



 Toray Group

Carbon Fiber

| DESCRIPTION | MATERIAL COMPATIBILITY | FIBER LENGTH | UNPACKED BULK DENSITY |
|------------------------------------|-----------------------------------|--------------------------------|---------------------------|
| Chopped Pellet (-65) | ABS, PET, PA, PC, TPU, POM | 6 mm (0.25 in.) | 425 g/L (minimum) |
| High Temp. Pellet (-83) | HPPA, PPO, PPA, PEEK, PAI, TPI | 6 mm (0.25 in.) | 350 g/L (minimum) |
| Chopped Pellet (-45) | ABS, PET, POM, PA, PA66 | 6 mm (0.25 in.) | 425 g/L (minimum) |
| Chopped Pellet (-95) | PA, PA66 | 6 mm (0.25 in.) | 350 g/L (minimum) |
| Chopped Pellet (-55) | PP & PE | 6 mm (0.25 in.) | 350 g/L (minimum) |
| Chopped Flake Dispersible (-02) | Water-Based Slurry Type | 3 - 50 mm (0.125 - 2.0 in.) | — |
| PX35 Milled Fiber | Various | 150 μ m (0.283 mils) | 490/ (95% carbon content) |
| PX30 Milled Fiber | Various | 150 μ m (0.283 mils) | 465/ (99% carbon content) |

**ZOLTEK™ PX35 tow is also available for D-LFT, LFT, and UD Tape applications.*

www.zoltek.com